

Main Menu	
Language	†
Configuration	>>>>
Setup	>>>>
Date & Time	>>>>
Shutdown	

† English/Deutsch/Russian/Romanian  
Portuguese/Espanol/Italiano

Navigate through the menus with the Left and Right buttons. Press the OK button to select an item. Pressing the Up button will go to the preceding menu. Items in **red** are the factory settings.



Configuration	
Reading timeout [6 sec]	1-100 seconds
ISO 24631-2	on/off
EIC/CIC Format	>>>>
Procedure	(select .rdf file)
Session	>>>>
Equivalence	>>>>
Reading sound	on/off
Send version (BT)	on/off
Send reading (BT)	EIC/CIC/None
Continuous Reading	on/off

Setup	
Timer backlight	1-40 seconds
Auto Shutdown	1-5 minutes
Audio Level	high/low/off
Display Brightness	high/mid/low
Keyboard sound	on/off
Start-up sound	on/off
Shut-down sound	on/off
Start-up image	on/off
Decimal separator	(comma/period)
Test unit	>>>>

Date & Time	
Format	EU/USA/Timestamp
Set date	(date dialog)
Set time	(time dialog)

EIC/CIC FORMAT	
EIC format	‡
Use retagging counter	on/off
CIC	long/short/none
Duplicate CIC allowed	on/off
Buzzer duplicate CIC	on/off

‡ Short/Long/Bi-HEX/HEX/ShortSA/  
BDN\_Ita/F210/Tiris

SESSION	
Continue	
New	
Open	
Delete	
Send/Print	
Modify/Erase	
Auto start new	on/off
Blank EIC allowed	on/off
Duplicate EIC allowed	on/off
Blank repetition	on/off
Send session (BT)	on/off
Send field name (BT)	on/off

Equivalence	
Show EIC/CIC	EIC/CIC
Browse	select from list
Search CIC	(dialog)

Test unit	
Autotuning RFID	
Cyclic Delay [min]	
Cyclic reading	
Cnt Reading	
Save RF	
Save HDX	
Save FDX-B	
Keyboard test	